1 Form A/1 Form C 10A Small power relays

LQ RELAYS (ALQ)

RoHS compliant

Protective construction: Sealed type

FEATURES

1. **Miniature size and small: 10(W) × 20(L) × 16(H) mm .394(W) × .787(L) × .630(H) inch**
2. **Compact with high capacity: 1 Form A and 1 Form C, 10 A**
3. **Class "F" coil is available**
4. **Contact rating at 105°C 221°F is approved by UL/C-UL (Class "F" coil only)**
   Please refer to "SAFETY STANDARDS" about the detail of contact rating.
5. **Surge 8,000 V, High breakdown voltage 4,000 V (Between contact and coil)**

TYPICAL APPLICATIONS

1. **Home appliances**
   - Refrigerators
   - Cooking ovens
   - Washing machine
   - Air conditioners
2. **Industrial equipment**
   - Motor control
   - Robot
   - Power supply

ORDERING INFORMATION

ALQ □ □ □

Contact arrangement
1: 1 Form C
3: 1 Form A

Coil insulation class
Nil: Class B insulation
F: Class F insulation

Nominal coil voltage (DC)
05: 5V, 06: 6V, 09: 9V, 12: 12V, 18: 18V, 24: 24V

Note: Certified by UL/C-UL, VDE and CQC

TYPES

Nominal coil voltage	Part No.	
	1 Form A	1 Form C
5V DC	ALQ305	ALQ105
6V DC	ALQ306	ALQ106
9V DC	ALQ309	ALQ109
12V DC	ALQ312	ALQ112
18V DC	ALQ318	ALQ118
24V DC	ALQ324	ALQ124

Standard packing: Carton 100 pcs., Case 500 pcs.

© Panasonic Corporation 2016

RATING

1. Coil data

Contact arrangement	Nominal coil voltage	Pick-up voltage (at 20°C 68°F)	Drop-out voltage (at 20°C 68°F)	Nominal operating current [±10%] (at 20°C 68°F)	Coil resistance [±10%] (at 20°C 68°F)	Nominal operating power (at 20°C 68°F)	Max. applied voltage
1 Form A	5V DC	75%V or less of nominal voltage (Initial)	5%V or more of nominal voltage (Initial)	40.0mA	125 Ω	200mW	180% of nominal voltage (at 20°C 68°F) 130% of nominal voltage (at 85°C 185°F)*4
	6V DC			33.3mA	180 Ω		
	9V DC			22.2mA	405 Ω		
	12V DC			16.7mA	720 Ω		
	18V DC			11.1mA	1,620 Ω		
	24V DC			8.3mA	2,880 Ω		
1 Form C	5V DC	75%V or less of nominal voltage (Initial)	5%V or more of nominal voltage (Initial)	80.0mA	62.5Ω	400mW	150% of nominal voltage (at 20°C 68°F) 110% of nominal voltage (at 85°C 185°F)*4
	6V DC			66.7mA	90 Ω		
	9V DC			44.4mA	202.5Ω		
	12V DC			33.3mA	360 Ω		
	18V DC			22.2mA	810 Ω		
	24V DC			16.7mA	1,440 Ω		

2. Specifications

Characteristics	Item		Specifications	
Contact	Arrangement		1 Form A	1 Form C
	Contact resistance (Initial)		Max. 100mΩ (By voltage drop 6 V DC 1 A)	
	Contact material		AgNi type	
Rating	Nominal switching capacity (resistive load)		5 A 30 V DC, 10 A 125 V AC, 5 A 250 V AC	N.O. side: 10 A 125 V AC, 5 A 250 V AC, 5 A 30 V DC N.C. side: 3 A 125 V AC, 2 A 250 V AC, 1 A 30 V DC
	Max. switching power (resistive load)		150 W, 1,250 VA	N.O. side: 150 W, 1,250 VA N.C. side: 30 W, 500 VA
	Max. switching voltage		250 V AC, 30 V DC	
	Max. switching current		N.O.: 10 A (125V AC), N.C.: 3 A (125V AC)	
	Nominal operating power		200 mW	400 mW
	Min. switching capacity (reference value)*1		100 mA, 5 V DC	
Electrical characteristics	Insulation resistance (Initial)		Min. 1,000 MΩ (at 500 V DC) Measurement at same location as “Breakdown voltage” section.	
	Breakdown voltage (Initial)	Between open contacts	1,000 Vrms for 1 min. (Detection current: 10 mA)	750 Vrms for 1 min. (Detection current: 10 mA)
		Between contact and coil	4,000 Vrms for 1 min. (Detection current: 10 mA)	
	Surge breakdown voltage*2 (Between contact and coil)		8,000 V (Initial)	
	Operate time (at nominal voltage) (at 20°C 68°F)		Max. 20 ms (excluding contact bounce time.) (Initial)	
	Release time (at nominal voltage) (at 20°C 68°F)		Max. 20 ms (excluding contact bounce time, with diode) (Initial)	
Mechanical characteristics	Shock resistance	Functional	1 Form A: 294 m/s², 1 Form C: 196 m/s² (Half-wave pulse of sine wave: 11 ms; detection time: 10μs.)	
		Destructive	980 m/s² (Half-wave pulse of sine wave: 6 ms.)	
	Vibration resistance	Functional	10 to 55 Hz at double amplitude of 1.6 mm (Detection time: 10μs.)	
		Destructive	10 to 55 Hz at double amplitude of 2.0 mm	
Expected life	Mechanical		Min. 10^7 (at 180 times/min.)	
Conditions	Conditions for operation, transport and storage*3		Ambient temperature: –40°C to +85°C –40°F to +185°F Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature)	
	Max. operating speed		20 times/min. (at nominal switching capacity)	
Unit weight			Approx. 7 g .25 oz	

* Specifications will vary with foreign standards certification ratings.

Notes: *1. This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.

*2. Wave is standard shock voltage of ±1.2×50μs according to JEC-212-1981

*3. The upper limit of the ambient temperature is the maximum temperature that can satisfy the coil temperature rise value. Refer to Usage, transport and storage conditions in NOTES.

© Panasonic Corporation 2016