

## Holders & Blocks for Low Voltage Supplementary Fuses

### 1 3/32" X 1 3/8" Fuses

Catalog Numbers	Volts	Page
BBS .....	600V .....	77

#### Holder


- HPS-L Panel mount holder .....322

#### Blocks

- BM Series, panel/DIN rail with adapters .....310
- 3723, 3742 and 3743 multi-pole add-on fuse blocks .....326



HPS-L



BM Series

### Pin Indicating Fuses

1/4" X 1 1/4" Fuse Catalog Numbers	Volts	Page
GBA 1/4" X 1 1/4" .....	125V .....	78
GLD 1/4" X 1 1/4" .....	125V .....	78
MIC 1 3/32" X 1 1/2" .....	250V .....	78
MIN 1 3/32" X 1 1/2" .....	250V .....	78
FNA 1 3/32" X 1 1/2" .....	250V .....	78
MIS 1 3/32" X 2" .....	600V .....	79
KAZ 1 3/32" X 2" .....	600V .....	79



HLD



HK Series

#### Holders

- 1/4" X 1 1/4": HLD Panel mount visual indication .....321
- 1/4" X 1 1/4": HK Series Panel mount lamp indicating .....321

#### Blocks

- 1/4" X 1 1/4": Series 8000 for visual indication .....324
- 1 3/32" X 1 1/2": 1-Pole signal block cat. # 3839 (not shown in catalog)\*
- 1 3/32" X 2": 1-Pole signal block cat. # 2778 (not shown in catalog)\*
- 1 3/32" X 2": 2-Pole signal block cat. # 2837 (not shown in catalog)\*
- 1 3/32" X 2": 3-Pole signal block cat. # 2838 (not shown in catalog)\*

\*Call our customer satisfaction team at 636-527-3877 for more information.



Series 8000

### Automotive Blade-type Fuses

Catalog Numbers	Volts	Page
ATC .....	32Vdc .....	82
ATM .....	32Vdc .....	82
MAX .....	32Vdc .....	83

#### Holders

- ATC: HHC, HHD, HHF, HHG & ATC-FHID In-line holders ..... 82
- ATM: HHL, HHM & ATM-FHID In-line holders ..... 83
- MAX: HHX In-line holders ..... 83



easyID™  
Illuminating Holders

HHC, HHD, HHF  
& HHG

HHL & HHM


HHX

### In-Line Rejecting and Non-Rejecting Fuses

Catalog Number	Volts	Page
GLQ rejecting fuse .....	300V .....	80
GMQ rejecting fuse .....	300V .....	80
GLR non-rejecting fuse .....	300V .....	81
GMF non-rejecting fuse .....	300V .....	81
GRF non-rejecting fuse .....	300V .....	81

#### Holders

- GLQ & GMQ: HLQ Rejection holder ..... 80
- GLR, GMF & GRF: HLR & HLR-2A non-rejection holders .....81



HLQ³ Fuse Holders



HLR Fuse Holder

Low Voltage Supplementary Fuses

# Cable Limiters & Welder Limiters

## K Series

### Specifications

**Description:** Cable limiters.

### Ratings:

- Volts — 600Vac
- IR — 200kA RMS Sym. @ 600Vac

### Agency Information:

UL Listing: KDM, KDR, KDP and KFM, KCM, KCM-B and KCR.

### Features and Benefits

- Sizes and ratings available to meet many applications.

### Typical Applications

- Protecting low voltage distribution and service entrance cables against short-circuit currents.

### Catalog Numbers

#### Copper Cable Limiter — 600 Volts

Catalog Number	Cable Size	Catalog Number	Cable Size
----------------	------------	----------------	------------

#### Tubular Terminals

KCY	#4	KCF	4/0
KCZ	#3	KCH	250 MCM
KCA	#2	KCJ <sup>1,2</sup>	350 MCM
KCB	#1	KCM <sup>1,2,3</sup> , KCM-B <sup>1</sup>	500 MCM
KCC	1/0	KCV	600 MCM
KCD <sup>1,2</sup>	2/0	KCR <sup>1,2</sup>	750 MCM
KCE	3/0	KCS	1000 MCM

#### Tubular Terminal and Offset Bolt-Type Terminal

KQV	#12	KDD <sup>1</sup>	2/0
KQT	#10	KDE	3/0
KFZ	#8	KDF	4/0
KIG	#6	KDH	250 MCM
KDY	#4	KDJ <sup>1,2</sup>	350 MCM
KDA	#2	KDM <sup>1,2,3</sup>	500 MCM
KDB	#1	KDU	600 MCM
KDC	1/0	KDR <sup>1,2</sup>	750 MCM

#### Compression Connector Rod and Tubular Terminals

KEX	4/0	KQO	350 MCM
KFH-A	250 MCM	KDT <sup>1</sup>	500 MCM

#### \*Center Bolt-Type Terminal and Off-Set Bolt-Type Terminal

KPF	4/0	KDP <sup>1</sup>	500 MCM
KFT <sup>1</sup>	250 MCM	KFM <sup>1</sup>	750 MCM
KEW <sup>1</sup>	350 MCM		

<sup>1</sup>Copper or aluminum cable; sizes of all other limiters pertain to copper only. KFM copper only. <sup>1</sup>UL Listed (File E90818).

<sup>2</sup>Available with shrink tube “\_V” suffix.

<sup>3</sup>Available with molded rubber boots. Add “-B” to end of part number.

## Accessories

Boots can be purchased separately.

For KCM BOOT-KCM

For KDM BOOT-KDM

Installation tools can be purchased separately from Thomas and Betts

• Crimp Tool: TBM-14M

• Die: 15506 KDM/15515 KDR

## 64000 & 68000 Series

### Specifications

**Description:** Welder limiters.

### Ratings:

- Volts — 600Vac (or less)
- IR — 200kA RMS Sym.

### Features and Benefits

- Current-limiting devices designed specially for use on welder circuits only
- Time-current characteristics are designed to hold on the intermittent overloading encountered in welder operation, while providing short-circuit protection to the circuit and equipment
- Welder limiters have excess current capacity in the operating range as needed for this type of service

### Typical Applications

- Welder circuits
- Because welder limiters have special characteristics, they are not intended for application on general-use circuits

### Catalog Numbers

Catalog Numbers	Fuse Holder Type	Nominal Amp Rating
68300	Class H	300
68600	Class H	600
64200	Class J	200
64300	Class J	300



## Recommended Fuse Blocks For 68000 & 64000 Series limiters

- See page 72

Data Sheet: 1045

Data Sheet: 1042