



Fuses for Semiconductor Protection

Cylindrical Fuses

Selection Guide Fuse-Holder ZS-Modul

ZS-Module	Number of Poles	Indicator Type	Part No.	Techn. Data [Page]	
10 x 38	1	-	51 063 04.DC	URZ 37	
10 x 38	1	-	51 063 04	URZ 37	
10 x 38	2	-	51 063 04.2	URZ 37	
10 x 38	3	-	51 063 04.3	URZ 37	
10 x 38	1	LED indicator	51 063 04.L	URZ 37	
10 x 38	2	LED indicator	51 063 04.2L	URZ 37	
10 x 38	3	LED indicator	51 063 04.3L	URZ 37	
14 x 51	1	-	51 058 04	URZ 37	
14 x 51	2	-	51 058 04.2	URZ 37	
14 x 51	3	-	51 058 04.3	URZ 37	
14 x 51	1	micro switch	51 058 04.S	URZ 37	
14 x 51	2	micro switch	51 058 04.2S	URZ 37	
14 x 51	3	micro switch	51 058 04.3S	URZ 37	
22 x 58	1	-	51 060 04	URZ 37	
22 x 58	2	-	51 060 04.2	URZ 37	
22 x 58	3	-	51 060 04.3	URZ 37	
22 x 58	1	micro switch	51 060 04.S	URZ 37	
22 x 58	3	micro switch	51 060 04.3S	URZ 37	

Selection Guide Fuse-Clips

Size	Part No.	Techn. Data [Page]	Type	
10 mm	61 017 01.2	URZ 35		
14 mm	61 001 01.2	URZ 35	screw	
22 mm	61 002 01.3	URZ 35	mountable	
27 mm	61 004 01.3	URZ 35		
14 mm	58 058 06	URZ 36	PCB	
22 mm	58 060 06	URZ 36	mountable	



Fuses for Semiconductor Protection

Cylindrical Fuses

Size
5 x 20 mm

Rated Voltage
AC 250 V

Class
aR

Rated Current [A]	Part No.	Rated Breaking Capacity [kA]	UL Rec.	Weight [kg/100]	Pack	
100 mA	70 001 40.0.100	300	✓	0.14	100	
125 mA	70 001 40.0.125	300	✓	0.14	100	
160 mA	70 001 40.0.160	300	✓	0.14	100	
200 mA	70 001 40.0.200	300	✓	0.14	100	
250 mA	70 001 40.0.250	300	✓	0.14	100	
315 mA	70 001 40.0.315	300	✓	0.14	100	
400 mA	70 001 40.0.400	300	✓	0.14	100	
500 mA	70 001 40.0.500	300	✓	0.14	100	
630 mA	70 001 40.0.630	300	✓	0.14	100	
800 mA	70 001 40.0.800	300	✓	0.14	100	
1	70 001 40.1	300	✓	0.14	100	
1.25	70 001 40.1.25	300	✓	0.14	100	
1.6	70 001 40.1.6	300	✓	0.14	100	
2	70 001 40.2	300	✓	0.14	100	
2.5	70 001 40.2.5	300	✓	0.14	100	
3.15	70 001 40.3.15	300	✓	0.14	100	
4	70 001 40.4	300	✓	0.14	100	
5	70 001 40.5	300	✓	0.14	100	
6.3	70 001 40.6.3	1 500 A		0.14	100	
8	70 001 40.8	1 500 A		0.14	100	
10	70 001 40.10	1 500 A		0.14	100	
6.3	70 007 40.6.3	300	✓	0.14	100	
8	70 007 40.8	300	✓	0.14	100	
10	70 007 40.10	300	✓	0.14	100	
12.5	70 007 40.12.5	300	✓	0.14	100	

A 0.79" (20 mm)
B 0.2" (5 mm)

