















| | | |
|---|--|----|
|  | Ordering | |
| | Mini contactor relays DILER, DILEEM, DILEM | |
| | Mini contactor relays, contactors | 2 |
| | Auxiliary contact modules | 6 |
| | Accessories | 8 |
| | Actuating voltages | 66 |
|  | DILA contactor relays | |
| | Contactor relays | 10 |
| | Auxiliary contact modules | 12 |
| | Actuating voltages | 68 |
|  | Technical overview | |
| | Contactors DILM, DILH | 14 |
|  | System overview | |
| | Contactors DILM, DILH | 16 |
|  | Ordering | |
| | Contactors DILM, DILH | |
| | Basic devices up to 170 A | 18 |
| | Complete units up to 170 A | 24 |
| | Standard devices greater than 170 A | 28 |
| | Comfort devices greater than 170 A | 30 |
| | Basic devices up to 200 A, 4 pole | 34 |
| | Auxiliary contact modules | 36 |
|  | Engineering | |
| | Auxiliary contact modules | 40 |
|  | Ordering | |
| | DILK contactors for capacitors | 41 |
|  | Engineering | |
| | Contactors for power factor correction | 42 |
|  | Ordering | |
| | Star-delta combinations SDAINL | 44 |
|  | Engineering | |
| | Star-delta combinations SDAINL | 46 |
|  | Ordering | |
| | DIUL reversing combinations | 48 |
|  | Description | |
| | CMD contactor monitoring device | 64 |
| | Ordering | |
| | CMD contactor monitoring device | 64 |

| | | |
|---|--|-----|
|  | Ordering | |
| | DILM contactor relays, DILM, DILH contactors | |
| | suppressor circuit | 50 |
| | Accessories | 52 |
|  | Ordering | |
| | Actuating voltages contactors DILM, DILH | |
| | Basic devices up to 170 A | 69 |
| | Basic devices up to 200 A, 4 pole | 74 |
| | Contactors up to 150 A | |
| | with electronic actuation | 76 |
| | Replacement coils | 71 |
| | Comfort devices greater than 170 A | 77 |
| | Standard devices greater than 170 A | 77 |
| | Electronic modules including coil | 77 |
| | Contactors for capacitors | 77 |
| | Engineering | |
| | Contact travel diagrams | 78 |
| | Enclosure | 79 |
| | UL/CSA-approved rating data | 80 |
| | UL/CSA special purpose ratings | 81 |
| | UL/CSA short circuit current rating | 82 |
| | Contactors for resistive loads | 84 |
| | Electrical life span | 86 |
| | Short-time loading | 90 |
| | Operating frequency | 91 |
| | Switching of DC current | 92 |
| | Technical data | |
| | Mini contactor relays, contactor relays | 93 |
| | Contactor monitoring device | 96 |
| | Basic devices up to 170 A | 104 |
| | Basic devices up to 200 A, 4 pole | 120 |
| | Comfort devices greater than 170 A | 112 |
| | Standard devices greater than 170 A | 112 |
| | Contactors for capacitors | 123 |
| | Contactors up to 150 A | |
| | with electronic actuation | 126 |
| | Lighting contactors | 125 |
| | Auxiliary contact modules | 128 |
| | Accessories | 128 |
| | Dimensions | |
| | Mini contactor relays | 130 |
| | Contactor relays | 131 |
| | Basic devices up to 170 A | 131 |
| | Basic devices up to 200 A, 4 pole | 133 |
| | Contactors larger than 170 A | 134 |
| | Contactors for capacitors | 136 |
| | Lighting contactors | 136 |
| | Contactor combinations | 137 |
| | Accessories | 138 |


1.1

Contactors

Mini contactors, relays

1 Ordering

Screw terminals



DILER mini contactor relays

| Rated operational current AC-15 | | Conventional free air thermal current | Contact | | Distinctive number | Circuit symbol | For use with |
|------------------------------------|-------|--|-----------------------------|------------------------------|-----------------------|----------------|--------------|
| 220 V | 380 V | | N/O = normally open contact | NC = normally closed contact | | | |
| 230 V | 400 V | | | | | | |
| 240 V | 415 V | | | | | | |
| I_e | I_e | I_{th} | | | | | |
| A | A | | A | | | | |
| 6 | 3 | 10 | 4 N/O | – | 40E | | DILE... |
| | | | 3 N/O | 1 NC | 31E | | DILE... |
| | | | 2 N/O | 2 NC | 22E | | DILE... |

Notes

- Coil terminal marking as specified in EN 50005
- Contact numbers to EN 50011
- The following applies to DC-operated contactors:
 - Integrated diode-resistor combination
 - Coil rating 2.6 W

Information relevant for export to North America



| Product Standards | IEC/EN 60947-4-1; UL508; CSA-C22.2 No.14-05; |
|-------------------|--|
| UL File No. | E29184 |
| UL CCN | NKCR |
| CSA File No. | 012528 |
| CSA Class No. | 3211-03 |
| NA Certification | UL Listed, CSA certified |