

Insulation coordination

| Parameter | Symbol | Unit | Value | Comment |
|--|-------------|------|-----------------------|---|
| Rms voltage for AC isolation test 50/60 Hz/1 min | U_d | kV | 4.3 | |
| Impulse withstand voltage 1.2/50 μ s | \dot{U}_w | kV | 8 | |
| Partial discharge extinction rms voltage @ 10 pC | U_e | V | 1650 | |
| Clearance (pri. - sec.) | d_{Cl} | mm | 8 | Shortest distance through air |
| Creepage distance (pri. - sec.) | d_{cp} | mm | 8 | Shortest path along device body |
| Case material | | | V0 according to UL 94 | |
| Comparative tracking index | CTI | | 600 | |
| Application example | - | - | 600 V CAT III PD2 | Reinforced insulation, non uniform field according to EN 50178 |
| Application example | - | - | 300 V CAT III PD2 | Reinforced insulation, non uniform field according to IEC 61010 |
| Application example | - | - | 1000 V CAT III PD2 | Simple insulation, non uniform field according to EN 50178, IEC 61010 |

Environmental and mechanical characteristics

| Parameter | Symbol | Unit | Min | Typ | Max | Comment |
|---|--------|--------------|-----|-----|-----|---------|
| Ambient operating temperature | T_A | $^{\circ}$ C | -40 | | 105 | |
| Ambient storage temperature | T_S | $^{\circ}$ C | -40 | | 105 | |
| Surrounding temperature according to UL 508 | | $^{\circ}$ C | | | 105 | |
| Mass | m | g | | 5 | | |

Electrical data HO 8-NSM/SP33-1000

 At $T_A = 25^\circ\text{C}$, $U_C = +3.3\text{ V}$, $N_P = 3$ turns, $R_L = 10\text{ K}\Omega$ unless otherwise noted (see Min, Max, typ. definition paragraph in page 12).

| Parameter | Symbol | Unit | Min | Typ | Max | Comment |
|--|---------------------|--------------------------------|---------------------|---------------------|---------------------|--|
| Primary nominal rms current | I_{PN} | At | | 8 | | |
| Primary current, measuring range | I_{PM} | At | -20 | | 20 | |
| Number of primary turns | N_P | | | 1,2,3 | | |
| Supply voltage | U_C | V | 3.14 | 3.3 | 3.46 | |
| Current consumption | I_C | mA | | | 25 | |
| Reference voltage | V_{ref} | V | 1.636 | 1.65 | 1.664 | Internal reference |
| External reference voltage | V_{ref} | V | 0.5 | | 1.85 | @ $U_C = 3.3 \approx 3.46\text{ V}$ |
| | | | 0.5 | | 1.7 | @ $U_C = 3.14 \approx 3.3\text{ V}$ |
| Output voltage range @ I_{PM} | $V_{out} - V_{ref}$ | V | -1.15 | | 1.15 | |
| Output voltage @ $I_P = 0\text{ A}$ | V_{out} | V | | $V_{ref} + V_{OE}$ | | |
| Electrical offset voltage | V_{OE} | mV | -7 | | 7 | |
| Temperature coefficient of V_{ref} | TCV_{ref} | ppm/K | | | ± 170 | -20 °C .. 85 °C Internal reference |
| | | | | | ± 180 | -40 °C .. 105 °C Internal reference |
| Temperature coefficient of V_{OE} | TCV_{OE} | mV/K | | | ± 0.080 | -40 °C .. 105 °C |
| Theoretical sensitivity | G_{th} | mV/A | | 57.5 | | 460 mV/ I_{PN} @ $U_C = 3.3\text{ V}$ |
| Sensitivity error | ϵ_G | % | | | ± 0.5 | Factory adjustment |
| Temperature coefficient of G | TCG | ppm/K | | | ± 200 | -20 °C .. 85 °C |
| | | | | | ± 210 | -40 °C .. 105 °C |
| Linearity error 0 .. I_{PN} | ϵ_L | % of I_{PN} | | | ± 0.5 | @ $U_C = 3.3\text{ V}$ |
| Linearity error 0 .. I_{PM} | ϵ_L | % of I_{PM} | | | ± 0.8 | @ $U_C = 3.3\text{ V}$ |
| Gain error with respect to $U_C \pm 10\%$ | | %/% | | | ± 0.4 | Gain error per U_C drift |
| Magnetic offset voltage @ $I_P = 0$ after $2.5 \times I_{PN}$ | V_{OM} | mV | | | ± 4 | |
| Reaction time @ 10 % of I_{PN} | t_{ra} | μs | | | 2 | $di/dt = I_{PN}/\mu\text{s}$ |
| Response time @ 90 % of I_{PN} | t_r | μs | | | 3.5 | $di/dt = I_{PN}/\mu\text{s}$ |
| Frequency bandwidth (-3 dB) | BW | kHz | | 250 | | |
| Output rms voltage noise (spectral density) (DC .. 100 kHz) | e_{no} | $\mu\text{V}/\sqrt{\text{Hz}}$ | | | 18.9 | |
| Output voltage noise (DC .. 20 MHz) | V_{no} | mVpp | | 40 | | |
| Standby pin "0" level | | V | | | 0.3 | |
| Standby pin "1" level | | V | $U_C - 0.3$ | | | |
| Time to switch from standby to normal mode | | μs | | | 20 | |
| Over-current detect | | At | $2.6 \times I_{PN}$ | $2.9 \times I_{PN}$ | $3.2 \times I_{PN}$ | peak value |
| Accuracy @ I_{PN} | X | % of I_{PN} | | | ± 1 | $= \epsilon_G + \epsilon_L$ |
| Accuracy @ I_{PN} @ $T_A = +85^\circ\text{C}$ | X | % of I_{PN} | | | ± 3.3 | See formula note ¹⁾ |
| Accuracy @ I_{PN} @ $T_A = +105^\circ\text{C}$ | X | % of I_{PN} | | | ± 4.1 | See formula note ¹⁾ |

Note: ¹⁾ Accuracy @ I_P and $X_{TA} = \pm [X + (TCG/10000) \cdot (T_A - 25) + TCV_{OE} \cdot 100 \cdot (T_A - 25) / (G_{th} \cdot I_P)]$.