

TEMPERATURE & PROCESS TECHNOLOGY

IEC PTFE Exposed Welded Tip Thermocouples with Miniature Thermocouple Plug



Type 'K'

Type 'J'

Type T'

- Thermocouple types K, J & T
- Fast response, welded exposed junction 1, 2, 5 or 10 metre lengths available
- Teflon[®] PTFE insulated twin-twisted lead
- 1/0.2mm conductors

•

•

.

- 'Re-Wireable' miniature flat pin plug
- Temperature range –75°C to +260°C
- Tolerance to IEC 584 Class 1
- Colour code to IEC 584-3
- Ideal for test & development applications

Т/С Туре	Conductors	Length	Termination	+Positive tail wire	-Negative tail wire code	order Code
'К'	1/0.2mm	2 m	Mini plug	Green	White	XF-1202-FAR
'К'	1/0.2mm	5 m	Mini plug	Green	White	XF-1215-FAR
'К'	1/0.2mm	10 m	Mini plug	Green	White	XF-1216-FAR
۲۲	1/0.2mm	1 m	Mini plug	Black	White	XF-1203-FAR
۲۲	1/0.2mm	2 m	Mini plug	Black	White	XF-1217-FAR
۲۲	1/0.2mm	5 m	Mini plug	Black	White	XF-1218-FAR
۲۲	1/0.2mm	10 m	Mini plug	Black	White	XF-1219-FAR
'T'	1/0.2mm	2 m	Mini plug	Brown	White	XF-1220-FAR
'T'	1/0.2mm	5 m	Mini plug	Brown	White	XF-1221-FAR

LABFACILITY

We are the largest UK

Measurement.

About Labfacility Formed in 1971, Labfacility specialize in the field of Temperature and Process

manufacturer of both temperature sensors and thermocouple connectors.

Quality & Service

Quality and Service are key elements in the continued growth of Labfacility.

Technical support is always freely available from our experienced technical sales teams and the company has ISO9001 accreditation.

Contact Details

Email sales@labfacility.com

Website www.labfacility.com