



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF23312-24B	x = 0.287 y = 0.284	1100 @ 0°C	618	6 ± 1	50,000 ± 20%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0							
TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			SIZE A	FSCM NO. 55335	DRAWING NO. BF23312-24B					
REV. NO. C	DESCRIPTION/ECO NUMBER X Y AND BRIGHTNESS RATINGS CHANGE	APPVD DATE 11/12/08	DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 11/12/08	SCALE NONE	RELEASED DATE 2/21/07	REVISION DATE 11/12/08	REV. NO. C	SHEET 1 OF 1

REV. NO. A	DESCRIPTION/ECO NUMBER CHANGE + ADDITIONAL DIMENSIONS	APPVD DATE 3/21/08
REV. NO. B	DESCRIPTION/ECO NUMBER BRIGHTNESS ±10% TO ±20%	APPVD DATE 6/13/08
REV. NO. C	DESCRIPTION/ECO NUMBER RELEASE & CANCEL P-0701-05	APPVD DATE 2/21/07