



Sensing Accessories

Mounting Brackets page 350

- Using the right bracket ensures optimum performance from your Banner sensors.
- Stainless steel and reinforced thermoplastic polyester mounts reduce installation time and lower total installed cost.
- Choice includes angled, through-hole brackets and split-clamp models that mount to a flat surface.
- Versatile swivel-mount models mount flat and have an adjustable ball to position the sensor at any angle.
- Custom brackets can be designed for your unique applications.



Quick-Disconnect (QD) Cables page 378

- Allow sensors to be replaced or moved quickly, minimizing downtime.
 - Pico- (M8), Euro-(M12), and Mini-styles are available for dc powered sensors.
 - Micro- and Mini-styles are available for ac powered sensors.
 - Choose straight or right-angle connectors.



Retroreflectors and Tape page 391

- Banner offers a complete line of high-quality acrylic targets, high-temperature targets and adhesive-backed retroreflective tapes (not shown).
- Numerous sizes, shapes and mounting options meet your application requirements.
- New high-reflectivity models dramatically increase sensing ranges, with reflectivity factors up to 3x.
- Maximum temperature ratings range from 50° to 480° C.
- Various mounting options are available.



EZ-LIGHT™ Indicator Lights page 402

- Indicator lights show the status of remote or inaccessible sensors, mimicking the sensor's indicators.
- Four model families are available: the 18 mm barrel-shaped, 18 or 30 mm T-style and the dome-shaped K50L.
- A single light displays multiple colors, eliminating the need for multiple post or stack lights.



Miscellaneous

Apertures and Aperture Kits	page 406
Replacement Lens Assemblies	408
Alignment Tools	409
Miscellaneous Accessories	410

