

International IOR Rectifier

SERIES IRK.136, .142, .162

**THYRISTOR/DIODE and
THYRISTOR/THYRISTOR**

NEW INT-A-pak Power Modules

Features

- High Voltage
- Electrically Isolated by DBC Ceramic (Al_2O_3)
- 3500 V_{RMS} Isolating Voltage
- Industrial Standard Package
- High Surge Capability
- Glass Passivated Chips
- Modules uses High Voltage Power thyristor/diodes in three Basic Configurations
- Simple Mounting
- UL E78996 approved 

135 A
140 A
160 A

Applications

- DC Motor Control and Drives
- Battery Charges
- Welders
- Power Converters
- Lighting Control
- Heat and Temperature Control

Major Ratings and Characteristics

| Parameters | IRK.136.. | IRK.142.. | IRK.162.. | Units | |
|---------------|-------------|-----------|-----------|--------------------|-------------------|
| $I_{T(AV)}$ | 135 | 140 | 160 | A | |
| @ T_C | 85 | 85 | 85 | °C | |
| $I_{T(RMS)}$ | 300 | 310 | 355 | A | |
| I_{TSM} | @ 50Hz | 3200 | 4500 | 4870 | A |
| | @ 60Hz | 3360 | 4712 | 5100 | A |
| I^2t | @ 50Hz | 51.5 | 102 | 119 | KA ² s |
| | @ 60Hz | 47 | 92.5 | 108 | KA ² s |
| $I^2\sqrt{t}$ | 515.5 | 1013 | 1190 | KA ² √s | |
| V_{RRM} | 400 to 1600 | | | V | |
| T_J range | -40 to 125 | | | °C | |

CASE STYLE NEW INT-A-PAK



IRK.136, .142, .162 Series

Bulletin I27117 rev. C 03/02

International
IR Rectifier

Electrical Specifications

Voltage Ratings

| Type number | Voltage Code | V_{RRM}/V_{DRM} , Maximum repetitive peak reverse voltage V | V_{RSM}/V_{DSM} , Maximum non-repetitive peak reverse voltage V | I_{RRM}/I_{DRM} @ 125°C mA |
|-------------|--------------|--|--|------------------------------------|
| IRK.136 | 04 | 400 | 500 | 50 |
| IRK.142 | 08 | 800 | 900 | |
| IRK.162 | 12 | 1200 | 1300 | |
| | 14 | 1400 | 1500 | |
| | 16 | 1600 | 1700 | |

Forward Conduction

| Parameter | IRK.136 | IRK.142 | IRK.162 | Units | Conditions |
|--|---------|---------|---------|-------------------|---|
| $I_{T(AV)}$ Max. average on-state current @ Case temperature | 135 | 140 | 160 | A | 180° conduction, half sine wave |
| | 85 | 85 | 85 | °C | |
| $I_{T(RMS)}$ Max. RMS on-state current | 300 | 310 | 355 | A | as AC switch |
| I_{TSM} Maximum peak, one-cycle on-state, non-repetitive surge current | 3200 | 4500 | 4870 | A | t = 10ms No voltage |
| | 3360 | 4712 | 5100 | | t = 8.3ms reappplied |
| | 2700 | 3785 | 4100 | | t = 10ms 100% V_{RRM} |
| | 2800 | 3963 | 4300 | | t = 8.3ms reappplied |
| I^2t Maximum I^2t for fusing | 51.5 | 102 | 119 | KA ² s | t = 10ms No voltage |
| | 47 | 92.5 | 108 | | t = 8.3ms reappplied |
| | 36.5 | 71.6 | 84 | | t = 10ms 100% V_{RRM} |
| | 33.3 | 65.4 | 76.7 | | t = 8.3ms reappplied |
| $I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing | 515.5 | 1013 | 1190 | KA ² s | t = 0.1 to 10ms, no voltage reappplied |
| $V_{T(TO)1}$ Low level value of threshold voltage | 0.86 | 0.83 | 0.8 | V | ($16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), @ T_J max. |
| $V_{T(TO)2}$ High level value of threshold voltage | 1.05 | 1 | 0.98 | | ($I > \pi \times I_{T(AV)}$), @ T_J max. |
| $r_{\theta 1}$ Low level value on-state slope resistance | 2.02 | 1.78 | 1.67 | mΩ | ($16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), @ T_J max. |
| $r_{\theta 2}$ High level value on-state slope resistance | 1.65 | 1.43 | 1.38 | | ($I > \pi \times I_{T(AV)}$), @ T_J max. |
| V_{TM} Maximum forward voltage drop | 1.57 | 1.55 | 1.54 | V | $I_{TM} = \pi \times I_{T(AV)}$, $T_J = 25^\circ\text{C}$, 180° conduction |
| I_H Maximum holding current | 200 | | | mA | Anode supply = 6V initial $I_r = 30A$, $T_J = 25^\circ\text{C}$ |
| I_L Maximum latching current | 400 | | | mA | Anode supply = 6V resistive load = 1Ω Gate pulse: 10V, 100μs, $T_J = 25^\circ\text{C}$ |

Switching

| | | | | |
|-----------------------------|----------|----|---|----------------------------------|
| t_{gd} Typical delay time | 1 | μs | $T_J = 25^\circ\text{C}$ | Gate Current=1A $dl/dt=1A/\mu s$ |
| t_{gr} Typical rise time | 2 | | $T_J = 25^\circ\text{C}$ | $V_d=0,67\% V_{DRM}$ |
| t_q Typical turn-off time | 50 - 200 | | $I_{TM} = 300A$; $-di/dt = 15A/\mu s$; $T_J = T_J$ max $V_r = 50V$; $dV/dt = 20V/\mu s$; Gate 0V, 100Ω | |

Blocking

| | | | | |
|-----------|--|------|------------------|---|
| I_{RRM} | Maximum peak reverse and off-state leakage current | 50 | mA | $T_J = 125^\circ\text{C}$ |
| I_{DRM} | | | | |
| V_{INS} | RMS isolation voltage | 3500 | V | 50Hz, circuit to base, all terminals shorted, $t = 1\text{s}$ |
| dV/dt | critical rate of rise of off-state voltage | 1000 | V/ μs | $T_J = T_J \text{ max.}$, exponential to 67% rated V_{DRM} |

Triggering

| Parameter | IRK.136 | IRK.142 | IRK.162 | Units | Conditions | |
|-------------|--|---------|---------|-------|------------------|---|
| P_{GM} | Max. peak gate power | | | 12 | W | $t_p \leq 5\text{ms}$, $T_J = T_J \text{ max.}$ |
| $P_{G(AV)}$ | Max. average gate power | | | 3 | W | $f = 50\text{Hz}$, $T_J = T_J \text{ max.}$ |
| I_{GM} | Max. peak gate current | | | 3 | A | $t_p \leq 5\text{ms}$, $T_J = T_J \text{ max.}$ |
| $-V_{GT}$ | Max. peak negative gate voltage | | | 10 | V | |
| V_{GT} | Max. required DC gate voltage to trigger | | | 4 | V | $T_J = -40^\circ\text{C}$ $T_J = 25^\circ\text{C}$ $T_J = T_J \text{ max.}$ Anode supply = 6V, resistive load; $R_a = 1\Omega$ |
| | | | | 2.5 | | |
| | | | | 1.7 | | |
| I_{GT} | Max. required DC gate current to trigger | | | 270 | mA | $T_J = -40^\circ\text{C}$ $T_J = 25^\circ\text{C}$ $T_J = T_J \text{ max.}$ Anode supply = 6V, resistive load; $R_a = 1\Omega$ |
| | | | | 150 | | |
| | | | | 80 | | |
| V_{GD} | Max. gate voltage that will not trigger | | | 0.3 | V | @ $T_J = T_J \text{ max.}$, rated V_{DRM} applied |
| I_{GD} | Max. gate current that will not trigger | | | 10 | mA | |
| di/dt | Max. rate of rise of turned-on current | | | 300 | A/ μs | @ $T_J = T_J \text{ max.}$, $I_{TM} = 400\text{A}$ rated V_{DRM} applied |

Thermal and Mechanical Specifications

| Parameter | IRK.136 | IRK.142 | IRK.162 | Units | Conditions | |
|------------|---|---------|---------|---------------|--|---|
| T_J | Max. junction operating temperature range | | | -40 to 125 | $^\circ\text{C}$ | |
| T_{stg} | Max. storage temperature range | | | -40 to 150 | $^\circ\text{C}$ | |
| R_{thJC} | 0.18 | 0.18 | 0.16 | K/W | DC operation, per junction | |
| R_{thCS} | Max. thermal resistance, case to heatsink | | | 0.05 | K/W | Mounting surface smooth, flat and greased Per module |
| T | Mounting IAP to heatsink | 4 to 6 | | Nm | A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads. | |
| | torque $\pm 10\%$ busbar to IAP | 4 to 6 | | | | |
| wt | Approximate weight | | | 200 (7.1) | g(oz) | |
| | Case Style | | | New Int-A-Pak | | |

ΔR Conduction (per Junction)

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

| Devices | Sinusoidal conduction @ $T_J \text{ max.}$ | | | | | Rectangular conduction @ $T_J \text{ max.}$ | | | | | Units |
|---------|--|--------|--------|--------|--------|---|--------|--------|--------|--------|-------|
| | 180° | 120° | 90° | 60° | 30° | 180° | 120° | 90° | 60° | 30° | |
| IRK.136 | 0.007 | 0.01 | 0.013 | 0.0155 | 0.017 | 0.009 | 0.012 | 0.014 | 0.015 | 0.017 | K/W |
| IRK.142 | 0.0019 | 0.0019 | 0.0020 | 0.0020 | 0.0021 | 0.0018 | 0.0022 | 0.0023 | 0.0023 | 0.0020 | |
| IRK.162 | 0.0030 | 0.0031 | 0.0032 | 0.0033 | 0.0034 | 0.0029 | 0.0036 | 0.0039 | 0.0041 | 0.0040 | |

IRK.136, .142, .162 Series


Bulletin I27117 rev. C 03/02

International
IOR Rectifier


Ordering Information Table

| Device Code | | | | |
|-------------|--|-----|---|----|
| IRK | T | 162 | / | 16 |
| ① | ② | ③ | | ④ |
| 1 | - Module Type | | | |
| 2 | - Circuit Configuration | | | |
| 3 | - Current Rating: $I_{T(AV)}$ | | | |
| 4 | - Voltage Code: Code x 100 = V_{RRM} | | | |


Outline Table




IRKT



IRKH



IRKL



NOTE: To order the Optional Hardware see Bulletin I27900




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current

IRK.136, .142, .162 Series

Bulletin I27117 rev. C 03/02

International
IR Rectifier




Fig.7 - On State Power Loss Characteristics




Fig.8 - On State Power Loss Characteristics




Fig.9 - On State Power Loss Characteristics




Fig. 10 - Current Ratings Characteristics




Fig. 11 - Current Ratings Characteristics




Fig. 12 - On-State Power Loss Characteristics




Fig. 13 - On-State Power Loss Characteristics




Fig. 14 - Maximum Non-Repetitive Surge Current




Fig. 15 - Maximum Non-Repetitive Surge Current

IRK.136, .142, .162 Series

Bulletin I27117 rev. C 03/02

International
IR Rectifier




Fig.16 - On State Power Loss Characteristics




Fig.17 - On State Power Loss Characteristics




Fig.18 - On State Power Loss Characteristics




Fig. 19 - Current Ratings Characteristics




Fig. 20 - Current Ratings Characteristics




Fig. 21 - On-State Power Loss Characteristics




Fig. 22 - On-State Power Loss Characteristics




Fig. 23 - Maximum Non-Repetitive Surge Current




Fig. 24 - Maximum Non-Repetitive Surge Current

IRK.136, .142, .162 Series

Bulletin I27117 rev. C 03/02

International
IR Rectifier




Fig.25 - On State Power Loss Characteristics




Fig.26 - On State Power Loss Characteristics




Fig.27 - On State Power Loss Characteristics




Fig.28 - On State Voltage Drop Characteristics




Fig.29 - On State Voltage Drop Characteristics




Fig.30 - On State Voltage Drop Characteristics




Fig.31 - Thermal Impedance ZthJC Characteristics




Fig.32 - Thermal Impedance ZthJC Characteristics




Fig.33 - Thermal Impedance ZthJC Characteristics

IRK.136, .142, .162 Series

Bulletin I27117 rev. C 03/02

International
IR Rectifier




Fig. 34 - Gate Characteristics

Data and specifications subject to change without notice.
This product has been designed and qualified for Multiple Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
03/02



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.