


CTG


Rating/ Characteristics	Absolute Maximum Ratings					Electrical Characteristics (Ta = 25°C)						Others																		
	V _{RSM} (V)	V _{RM} (V)	I _O (A)	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V)	I _R (mA)	I _{R(H)} (mA)	t _{rr} (μs)	I _F /I _{RP} (mA)	Outline Drawing	Weight(g)	Taping	Note															
Type No.	per chip		With Fin	50Hz Half-Sine Wave Single Pulse			Max. per chip	I _F (A)	V _R = V _{RM} max(per chip)	V _R = V _{RM} , T _J = 140°C max (per chip)																				
CTG-11S	70	70	5.0	35	-40 ~ +140		1.3	2.5		1.5	0.1	100/100	⑥⑥	2.6	—	For High Frequency Rectification														
CTG-11R	70	70																												
CTG-12S	200	200																												
CTG-12R	200	200																												
CTG-14S	400	400																												
CTG-14R	400	400																												
CTG-21S	70	70	10	65				5.0	0.5	2.5			0.1	100/100			⑥⑥	2.6	—	For High Frequency Rectification										
CTG-21R	70	70																												
CTG-22S	200	200																												
CTG-22R	200	200																												
CTG-23S	300	300																												
CTG-23R	300	300	8.0					10	1.0	5.0							⑥⑦	6.1				For High Frequency Rectification								
CTG-24S	400	400																												
CTG-24R	400	400																												
CTG-31S	70	70	20	150				10	1.0	5.0											⑥⑦		6.1		For High Frequency Rectification					
CTG-31R	70	70																												
CTG-32S	200	200																												
CTG-32R	200	200																												
CTG-33S	300	300																												
CTG-33R	300	300	16	100				10	1.0	5.0																				
CTG-34S	400	400																												
CTG-34R	400	400																												

Thermal Resistance R_{th(j-c)}: 3.0°C/W (CTG-11S~24R)
1.5°C/W (CTG-31S~34R)

Outline Drawing ⑥⑥







Outline Drawing ⑥⑦



Center Tap Internal Connection: S Type R Type

⑥⑥⑦ Plastic Molded, Flammability: UL94V-0 or Equivalent


CTG-1 Series

I_F-V_F Characteristics (CTG-11)P_{F(AV)}-I_{F(AV)} Characteristics (CTG-11)I_{F(AV)}-T_c Deratings (CTG-11)I_F-V_F Characteristics (CTG-12)


CTG-1 Series

CTG-1 Series


PF(AV)-IF(AV) Characteristics (CTG-12)




IF(AV)-Tc Deratings (CTG-12)




IF-VF Characteristics (CTG-14)



PF(AV)-IF(AV) Characteristics (CTG-14)




IF(AV)-Tc Deratings (CTG-14)




CTG-2 Series


IF(AV)-Tc Deratings (CTG-21)




IF(AV)-Tc Deratings (CTG-22)




IF-VF Characteristics (CTG-23)




PF(AV)-IF(AV) Characteristics (CTG-23)




IF(AV)-Tc Deratings (CTG-23)




IF-VF Characteristics (CTG-24)



PF(AV)-IF(AV) Characteristics (CTG-24)




IF(AV)-Tc Deratings (CTG-24)




CTG-3 Series


IF(AV)-Tc Deratings (CTG-31)




IF(AV)-Tc Deratings (CTG-32)




IF-VF Characteristics (CTG-33)




PF(AV)-IF(AV) Characteristics (CTG-33)




IF(AV)-Tc Deratings (CTG-33)




IF-VF Characteristics (CTG-34)



PF(AV)-IF(AV) Characteristics (CTG-34)



IF(AV)-Tc Deratings (CTG-34)




Symbols/trr Measurement Circuit

Symbols

V_{RSM}	Peak Reverse Surge Voltage	I_{RSM}	Peak Reverse Surge Current	T_{stg}	Storage Temperature
V_{RM}	Peak Reverse Voltage	I_R	Reverse Current	t_{rr}	Reverse Recovery Time
V_{P-P}	Reverse Voltage (Peak to Peak)	I_{RP}	Peak Reverse Current	C_t	Total Capacitance Between Terminals
V_R	Reverse Voltage	$I_{R(H)}$	Reverse Current (High Temperature)	$R_{th(j-c)}$	Thermal Resistance, Junction to Case
V_F	Forward Voltage	I_Z	Avalanche Current	r_z	Temperature Coefficient of Breakdown Voltage
V_B	Breakdown Voltage	I_{ZSM}	Allowable Avalanche Current	R_z	Equivalent Resistance of Breakdown Region
I_o	Average Rectified Forward Current	T_a	Ambient Temperature	$P_{F(AV)}$	Average Forward Power Dissipation
I_F	Forward Current	T_J	Junction Temperature	I^2_t	I^2_t limiting Value
$I_{F(AV)}$	Average Forward Current	T_{opr}	Operating Ambient Temperature		
I_{FSM}	Peak Forward Surge Current	T_c	Case Temperature		

Reverse Recovery Time Measurement Circuit



Taping Specifications

Excluding High Voltage Diodes


Designation	Dimension (in mm)	Packaging Dimension and Marking	Quantity
V Add Suffix [V] to Type No.	Tape Carrier Method <p>(1) Right side of taping direction is cathode. (2) Place electrode side down when casing. (3) Provide leader tape of 150~200mm at beginning of tape. (4) Provide space of more than 10 pitches each for beginning and end of tape.</p>	Reel Marking of Type No., Lot No. and Quantity 	1,800 pcs per reel
V Add Suffix [V] to type No.	Axial Taping 	Reel Markings of Type No. Lot No. and Quantity 	5,000 pcs per reel (2.7φ body) 3,000 pcs per reel (4.0φ body)

Taping Specifications

6


Marking Guide

1 Small TMD




- ① Type Designation (in abbreviation)
AM01 is abbreviated as M.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
- ③ A: Year (Last Number of AD Year)
B: Month (Jan. to Sept. are represented by numbers 1 to 9 respectively, and Oct., Nov., and Dec. are abbreviated as O, N and D respectively)
- ④ Cathode Band: Successive Band, however AU02 Type is Non-Successive Band.

2 E/EO Type TMD



- ① Type Designation (in abbreviation)
EM01 is abbreviated as MO, EM2 is abbreviated as M2.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
B: 800 V, C: 1000V, F: 1500V
However, EU02A to be marked 2A, and EU2YX to be marked Y.
- ③ Abbreviations Representing Production Period
A: Year (Last Number of AD Year)
B: Month (1~9, 0, N, D)
- ④ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days


3 R Type TMD



- ① Type Designation: Mark in 2 sets
- ② Production Period: Mark in 4 sets
A: Year (Last Number of AD Year)
B: Month (1~9, 0, N, D)
- ③ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days
- ④ Cathode Band Color: Silver: For Power Supply
Yellow: For Middle Speed
Red : For High Speed and Ultra-High Speed


4 RB40/60

(RB40 Series)




- ① Peak Reverse Voltage Designation
1, 2, 4, 6, C
- ② Production Period
- ③ Year (Last Number of AD Year)
- ④ Month (1~9, 0, N, D)
- ⑤ Divided in 3 ten day terms
A: 1st 10days, B: 2nd 10days
C: 3rd 10days
- ⑥ Color Designation: Silver

(RB60 Series)




Dot Designation RB601 Violet
RB602 No Color
RB604 Blue
RB606 White

5 RBV/RBA




- ① Type Designation
- ② Lot Number
1st : Year (Last Number of AD Year)
2nd: Month (1~9, 0, N, D)
3rd : Divided 1~3 ten day Terms
A: 1st 10 days B: 2nd 10 days
C: 3rd 10 days
- ③ In-Put Designation

6 TO220 Type (FM or CT Type)




- ① Type Designation
Show FMU-12S as FMU12S.
- ② Polarity: Rectifier Symbols
- ③ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, 0, N, D)
3rd, 4th: Day

7 TO220 Type (FM or CT Type, single chip)




- ① Type Designation: Omit Last Letter
Show FML-G12S as FMLG12.
- ② Last Letter of Type Designation
- ③ Polarity: Rectifier Symbols
- ④ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, 0, N, D)
3rd, 4th: Day

8 TO3P Type (FM or CT Type)




- ① Type shown in full designation
However, CTB-34/34S/34M are marked as CTB-34, CTU-G3DR is marked as CTUG3DR.
- ② Polarity: Rectifier Symbols
- ③ Lot Number:
1) M, U, G and L Types
First Number : Last Digit of AD Year
Second Number : Month
Third and Fourth Numbers: Day
Fifth Number : None
2) For types CTB-34/34S/34M, the fifth letter shows type designation. If no fifth number, the type is CTB-33 or CTB-34.
- 3) Marking Color: Silver

9 MI-10/15 Type



- ① MI-10/15 is die-stamped on the top of the case.
- ② Rectifier Symbols
- ③ Lot Number:
First Number : Peak Reverse Voltage:
(Letter) 0=50V, 1=100V, 2=200V,
4=400V, 6=600V, C=1000V
Second Number : Last Digit of AD Year
Third Number : Month
Fourth and Fifth Numbers: Day
Sixth Number : Production number and
U: Voltage Doubler Type

10 SFP Type



- ① Type Designation:
SFPB-64 is abbreviated at B64.
- ② Cathode Band