

Modular system

Single-axis inverter IndraDrive M - HMS



Modular system

Single-axis inverter ■ IndraDrive M - HMS**Documentation**

- Operating instructions
- Project planning manual

Technical data

		HMS01.1N-W0020	HMS01.1N-W0036	HMS01.1N-W0054	HMS01.1N-W0070	HMS01.1N-W0110
Performance data						
Continuous current	[A]	12.1	21.3	35	42.4	68.5
Maximum current	[A]	20	36	54	70.7	110
Motor rated capacity, typical	[kW]	5.5	11	18.5	22	0
Input voltage	[V]	DC 254...750 V				
Intermediate circuit						
Switching frequency/max. output frequency	4 kHz	0 ... 400 Hz				
	8 kHz	0 ... 800 Hz				
	12 kHz	0...1200 Hz				
	16 kHz	0...1600 Hz				
Output voltage	[V]	3 x AC 0...500 V				
DC bus voltage	[V] DC	254...750 V				
Control voltage						
Power consumption without control unit and motor brake	[W]	10	15	10	16	34
Protection						
EMC		EN 61800-3 [↔]				
Cooling type		Air cooling				
Norms and Standards						
Certification		EN 61800-5-1 [↔] UL 508 C [↔]				
Weight						
Weight	[kg]	5.27		6.68	7.94	11.06
		HMS01.1N-W0150	HMS01.1N-W0210	HMS01.1N-W0350	HMS02.1N-W0028	HMS02.1N-W0054
Performance data						
Continuous current	[A]	99.7	150.7	250	13.82	25
Maximum current	[A]	150	210	350	28.3	54

Modular system

Single-axis inverter ■ IndraDrive M - HMS

Motor rated capacity, typical	[kW]	55	75	0		
Input voltage	[V]	DC 254...750 V				
Intermediate circuit						
Switching frequency/max. output frequency	4 kHz	0 ... 400 Hz				
	8 kHz	0 ... 800 Hz				
	12 kHz	0...1200 Hz			0...1200 Hz	
	16 kHz	0...1600 Hz		0...1600 Hz		
Output voltage	[V]	3 x AC 0...500 V				
Intermediate circuit capacity	[mF]	0	4.9	0.135	0.27	
DC bus voltage	[V] DC	254...750 V				
Control voltage						
Power consumption without control unit and motor brake	[W]	23	75	218	13	17
Protection						
EMC		EN 61800-3 ↔				
Cooling type		Air cooling				
Norms and Standards						
Certification		EN 61800-5-1 ↔ UL 508 C ↔				
Weight						
Weight	[kg]	12.74	16.44	31.7	3.5	5

Dimensions

		HMS01.1N-W0020	HMS01.1N-W0036	HMS01.1N-W0054	HMS01.1N-W0070	HMS01.1N-W0110
Dimensions						
Height H	[mm]	440	440	440	440	440
Width B	[mm]	50	50	75	100	125
Depth T	[mm]	262	262	262	262	262
		HMS01.1N-W0350	HMS01.1N-W0210	HMS01.1N-W0150	HMS02.1N-W0028	HMS02.1N-W0054
Dimensions						
Height H	[mm]	440	440	440	352	352
Width B	[mm]	350	200	150	50	75
Depth T	[mm]	262	262	262	205	205

Components

Description	Page	Details
Servo drives	Firmware 1G	IndraDrive (MPH, MPB, MPD, MPC)

Modular system

Single-axis inverter ■ IndraDrive M - HMS

Description	Page	Details
Servo drives	Firmware 2G	IndraDrive (MPE, MPB/MPM, MPC)
Servo drives	Control units 1G	IndraDrive (BASIC, ADVANCED)
Servo drives	Control units 2G	IndraDrive (ECONOMY, BASIC, ADVANCED)

Bosch Rexroth AG

Postfach 13 57
97803 Lohr, Germany
Bgm.-Dr.-Nebel-Str. 2
97816 Lohr, Germany
Tel. +49 9352 18-0
Fax +49 9352 18-8400
www.boschrexroth.com/electrics

Local contact information can be found at:

www.boschrexroth.com/adressen

The data specified above only serve to describe the product. As our products are constantly being further developed, no statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification.

It must be remembered that our products are subject to a natural process of wear and aging.