


## Ordering Information

Sensors [Refer to *Dimensions* on page 10.]


### DC 2-Wire, Pre-wired Models

| Size  | Sensing distance |        | Output                  | Operation mode | Model            |
|---|------------------|--------|-------------------------|----------------|------------------|
| Shielded<br> | M8               | 1.5 mm | DC 2-Wire<br>(polarity) | NO             | E2FM-X1R5D1 2M * |
|   | M12              | 2 mm   |                         |                | E2FM-X2D1 2M *   |
|   | M18              | 5 mm   |                         |                | E2FM-X5D1 2M *   |
|   | M30              | 10 mm  |                         |                | E2FM-X10D1 2M *  |


Note: Models with NC operation are also available. Ask your OMRON representative for details.

\* Fluororesin-coated models are also available. The model numbers are E2FM-QX□D1. The cable material, however, is vinyl chloride and requires separate protection.

### DC 2-wire Pre-wired Smartclick Connector Models (M12)


| Size  | Sensing distance |        | Output                           | Operation mode | Model                   |
|---|------------------|--------|----------------------------------|----------------|-------------------------|
| Shielded<br> | M8               | 1.5 mm | Polarity Pin allocations: 1-4    | NO             | E2FM-X1R5D1-M1TGJ 0.3M  |
|   |                  |        | No polarity Pin allocations: 3-4 |                | E2FM-X2D1-M1TGJ 0.3M    |
|   | M12              | 2 mm   | Polarity Pin allocations: 1-4    |                | E2FM-X2D1-M1TGJ-T 0.3M  |
|   |                  |        | No polarity Pin allocations: 3-4 |                | E2FM-X5D1-M1TGJ 0.3M    |
|   | M18              | 5 mm   | Polarity Pin allocations: 1-4    |                | E2FM-X5D1-M1TGJ-T 0.3M  |
|   |                  |        | No polarity Pin allocations: 3-4 |                | E2FM-X10D1-M1TGJ 0.3M   |
|   | M30              | 10 mm  | Polarity Pin allocations: 1-4    |                | E2FM-X10D1-M1TGJ-T 0.3M |
|   |                  |        | No polarity Pin allocations: 3-4 |                |                         |

### DC 3-Wire, Pre-wired Models

| Size   | Sensing distance |        | Model                        |                              |
|--|------------------|--------|------------------------------|------------------------------|
|  |                  |        | Output configuration: NPN NO | Output configuration: PNP NO |
| Shielded<br> | M8               | 1.5 mm | E2FM-X1R5C1 2M               | E2FM-X1R5B1 2M               |
|  | M12              | 2 mm   | E2FM-X2C1 2M                 | E2FM-X2B1 2M                 |
|  | M18              | 5 mm   | E2FM-X5C1 2M                 | E2FM-X5B1 2M                 |
|  | M30              | 10 mm  | E2FM-X10C1 2M                | E2FM-X10B1 2M                |

Note: Models with NC operation are also available. Ask your OMRON representative for details.

### DC 3-Wire, M12 Connector Models




| Size  | Sensing distance |        | Model                        |                              |
|---|------------------|--------|------------------------------|------------------------------|
|   |                  |        | Output configuration: NPN NO | Output configuration: PNP NO |
| Shielded<br> | M8               | 1.5 mm | E2FM-X1R5C1-M1               | E2FM-X1R5B1-M1 *             |
|   | M12              | 2 mm   | E2FM-X2C1-M1                 | E2FM-X2B1-M1 *               |
|   | M18              | 5 mm   | E2FM-X5C1-M1                 | E2FM-X5B1-M1 *               |
|   | M30              | 10 mm  | E2FM-X10C1-M1                | E2FM-X10B1-M1 *              |

\* Fluororesin-coated models are also available. The model numbers are E2FM-QX□B1-M1. The cable material, however, is vinyl chloride and requires separate protection.

## Accessories (Order Separately)

### Sensor I/O Connectors (M12, Sockets on One Cable End)

(Models for Connectors and with Pre-wired Connectors: A Connector is not provided with the Sensor. Be sure to order a Connector separately.)  
**[Refer to XS2, XS5.]**

| Appearance  | Cable length | Sensor I/O Connector model number | Applicable Proximity Sensor model number |
|---|--------------|-----------------------------------|--|
|  | 2m           | XS2F-D421-DC0-F                   | E2FM-X□C1-M1<br>E2FM-X□B1-M1             |
|   | 5m           | XS2F-D421-GC0-F                   |  |
|  | 2m           | XS2F-D422-DC0-F                   |  |
|   | 5m           | XS2F-D422-GC0-F                   |  |
|  | 2m           | XS5F-D421-D80-F                   | E2FM-X□D1-M1TGJ<br>E2FM-X□D1-M1TGJ-T     |
|   | 5m           | XS5F-D421-G80-F                   |  |

Note1. Refer to your OMRON website for details on the XS2 and XS5.

## Ratings and Specifications

### DC 2-Wire (E2FM-X□D□)

| Item  | Size                      | M8  | M12   | M18                  | M30                  | M12  | M18                  | M30                  |  |
|---|---------------------------|---|---|----------------------|----------------------|--|----------------------|----------------------|--|
|   | Shielded Model            | E2FM-X1R5D1-□   | E2FM-X2D1-□   | E2FM-X5D1-□          | E2FM-X10D1-□         | E2FM-X2D1-M1T1GJ-T   | E2FM-X5D1-M1T1GJ-T   | E2FM-X10D1-M1T1GJ-T  |  |
| <b>Sensing distance</b>                                 |                           | 1.5 mm±10%  | 2 mm±10%  | 5 mm±10%             | 10 mm±10%            | 2 mm±10%   | 5 mm±10%             | 10 mm±10%            |  |
| <b>Set distance</b>                                     |                           | 0 to 1.05 mm  | 0 to 1.4 mm   | 0 to 3.5 mm          | 0 to 7 mm            | 0 to 1.4 mm  | 0 to 3.5 mm          | 0 to 7 mm            |  |
| <b>Differential travel</b>                              |                           | 15% max. of sensing distance  |   |                      |                      |  |                      |                      |  |
| <b>Sensing object</b>                                   |                           | Ferrous metal (The sensing distance decreases with non-ferrous metal. Refer to <i>Engineering Data</i> on page 7.)                                |   |                      |                      |  |                      |                      |  |
| <b>Standard sensing object</b>                          |                           | Iron, 8 × 8 × 1 mm  | Iron, 12 × 12 × 1 mm  | Iron, 30 × 30 × 1 mm | Iron, 54 × 54 × 1 mm | Iron, 12 × 12 × 1 mm                                       | Iron, 30 × 30 × 1 mm | Iron, 54 × 54 × 1 mm |  |
| <b>Response frequency *1</b>                            |                           | 200 Hz  | 100 Hz  | 100 Hz               | 50 Hz                | 100 Hz   | 100 Hz               | 50 Hz                |  |
| <b>Power supply voltage (operating voltage range)</b>   |                           | 12 to 24 VDC (10 to 30 VDC), ripple (p-p): 10% max.   |   |                      |                      |  |                      |                      |  |
| <b>Leakage current</b>                                  |                           | 0.8 mA max.   |   |                      |                      |  |                      |                      |  |
| <b>Output configuration</b>                             |                           | With polarity   |   |                      |                      | No polarity  |                      |                      |  |
| <b>Control output</b>                                   | <b>Switching capacity</b> | 3 to 100 mA   |   |                      |                      |  |                      |                      |  |
|   | <b>Residual voltage</b>   | 3 V max.<br>(Load current: 100 mA max., Cable length: 2 m)  |   |                      |                      | 5 V max.<br>(Load current: 100 mA max., Cable length: 2 m) |                      |                      |  |
| <b>Indicators</b>                                       |                           | Operation indicator (red LED), Setting/Operation indicator (green LED)  |   |                      |                      |  |                      |                      |  |
| <b>Operation mode (with sensing object approaching)</b> |                           | NO *2   |   |                      |                      |  |                      |                      |  |
| <b>Protection circuits</b>                              |                           | Surge suppressor, Load short-circuit protection   |   |                      |                      |  |                      |                      |  |
| <b>Ambient temperature range</b>                        |                           | Operating/Storage: -25 to 70°C (with no icing or condensation)  |   |                      |                      |  |                      |                      |  |
| <b>Ambient humidity range</b>                           |                           | Operating/Storage: 35% to 95% (with no condensation)  |   |                      |                      |  |                      |                      |  |
| <b>Temperature influence</b>                            |                           | ±20% max. of sensing distance at 23°C in the temperature range of -25 to 70°C.  |   |                      |                      |  |                      |                      |  |
| <b>Voltage influence</b>                                |                           | ±1% max. of sensing distance at rated voltage in the rated voltage ±15% range   |   |                      |                      |  |                      |                      |  |
| <b>Insulation resistance</b>                            |                           | 50 MΩ min. (at 500 VDC) between current-carrying parts and case   |   |                      |                      |  |                      |                      |  |
| <b>Dielectric strength</b>                              |                           | 1,000 VAC, 50/60 Hz for 1 minute between current-carrying parts and case  |   |                      |                      |  |                      |                      |  |
| <b>Vibration resistance</b>                             |                           | Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y, and Z directions  |   |                      |                      |  |                      |                      |  |
| <b>Shock resistance</b>                                 |                           | Destruction: 500 m/s <sup>2</sup><br>10 times each in X, Y, and Z directions  | Destruction: 1,000 m/s <sup>2</sup> 10 times each in X, Y, and Z directions |                      |                      |  |                      |                      |  |
| <b>Degree of protection</b>                             |                           | IEC 60529 IP67  |   |                      |                      |  |                      |                      |  |
| <b>Connection method</b>                                |                           | Unmarked: Pre-wired Models (Standard cable length: 2 m)<br>Models ending with -M1GJ-□: Pre-wired Connector Models (Standard cable length: 300 mm) |   |                      |                      |  |                      |                      |  |