

\*\*\* SPARE PART\*\*\* SIMATIC DP, ELECTRONIC MODULE  
DIGITAL, FOR ET 200B, W=160MM, 16DI 24V DC, STANDARD

### Supply voltage

Rated value (DC)	24 V; L3+; value at t < 0.5 s: 35 V
permissible range, lower limit (DC)	18.5 V
permissible range, upper limit (DC)	30.2 V

### Input current

Current consumption, typ.	70 mA; from L3+; logic
Current consumption, max.	500 mA; from L3+; sensor
$I^2t$	0.05 A <sup>2</sup> ·s; with starting current inrush

### Power loss

Power loss, typ.	2.5 W
------------------	-------

### Hardware configuration

Rack	
<ul style="list-style-type: none"> <li>required terminal block</li> </ul>	TB1/DC, TB1-4/DC, TB3/DC, TB3-4/DC

### Digital inputs

Number of digital inputs	16
--------------------------	----

Input voltage	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	-30 to +5V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	13 to 30V

Input current	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	4 mA; At 24 V min. 2 mA

Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> <li>at "0" to "1", min.</li> </ul>	2 ms
<ul style="list-style-type: none"> <li>at "0" to "1", max.</li> </ul>	3.5 ms

Cable length	
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	100 m

### Encoder

Connectable encoders	
<ul style="list-style-type: none"> <li>2-wire sensor</li> </ul>	Yes
<ul style="list-style-type: none"> <li>permissible quiescent current (2-wire sensor), max.</li> </ul>	1.5 mA

### Interfaces

PROFIBUS DP	
• Transmission rate, max.	12 Mbit/s
• FREEZE capability	Yes
Protocols	
Bus protocol/transmission protocol	PROFIBUS DP
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• RUN LED	Yes
• Bus fault BF (red)	Yes
• Status indicator digital input (green)	Yes
Potential separation	
between electronic block and PROFIBUS DP	Yes
Potential separation digital inputs	
• Potential separation digital inputs	No
Degree and class of protection	
Degree of protection acc. to EN 60529	IP20
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C; 40°C for other mountings
Air pressure acc. to IEC 60068-2-13	
• permissible range, lower limit	795 hPa
• permissible range, upper limit	1 080 hPa
Relative humidity	
• Operation, min.	15 %
• Operation, max.	95 %; RH class 2 in accordance with IEC 1131-2
Vibrations	
• Operation, tested according to IEC 60068-2-6	Yes; IEC 68, Part 2-6; 10 to 57 Hz; (constant amplitude 0.075 mm); 57 to 150 Hz; (constant acceleration 1 g)
Shock test	
• tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27; half-sine, 15 g, 11 ms
Connection method	
Design of electrical connection for the inputs and outputs	Screw-type and spring-loaded terminals, permanent wiring; 3 and 4-wire connection
Dimensions	
Width	160 mm; EB and TB
Height	130 mm; EB and TB
Depth	60 mm; EB and TB
Weights	

---

Weight, approx.

600 g; EB and TB

**last modified:**

03/01/2017